

LW-ODB-16A Fiber Terminal Box FTB - 16 Fibers



Description:

Fiber Terminal Box FTB provides fiber optic cable management for the connection of distribution cables and drop cables at the user access point in fiber optic network. Linkwell provides Fiber Terminal Box FTB made of high quality PC and ABS plastic alloy and SMC material from 2 fibers to 96 fibers.

LW-ODB-16A Fiber Terminal Box FTB integrates fiber cable fixation, storage, splicing and distribution in an outdoor and indoor wall mounting and outdoor pole mounting box.

Features:

- Burglar-proof padlock
- Efficient cable management
- UV protection and anti-aging material
- Water-proof design with IP65 Protection level
- Integrated with splice tray and cable management system

- Fiber bending radius control more than 40mm
- Suitable for the fusion splice or mechanical splice
- 1×8 or 1×16 blockless splitter can be installed as an option

Specification:

Max. Capacity	SC: 16 fibers LC: 32 fibers
Max. Inlet Cable Diameter	18mm
Inlet Cable Number	2 cable glands or 1 uncut cable port
Max. Outlet Cable Diameter	4.6mm
Outlet Cable Number	16pcs
Protection Grade	IP65
Installation Method	Wall mounting and pole mounting (pole ring is optional)
Working Environment	Outdoor and indoor
Dimension	293(H)*219(W)*84(D)mm
Net Weight	1.5 KG
Gross Weight	2.3 KG (Without adaptors/Pigtails)

Ordering Information: LW-ODB-16A-XX-XX-XX-XX-XX-XX:

Model	LW-ODB-16A
XX: Adapter	None: without adapter SC: SC/UPC SA: SC/APC LC: LC/UPC LA: LC/APC
XX: Pigtail	None: without pigtail SC: SC/UPC SA: SC/APC LC: LC/UPC LA: LC/APC
XX: Splitter	None: without splitter B12: 1×2 B14: 1×4 B18: 1×8 B116: 1×16
XX: Inlet Cable Port	CG: waterproof cable gland UN: uncut cable port
XX: Mounting Method	W: wall mounting P: pole mounting
XX: Box Color	G: gray B: black