



TBS6909-X

TBS6909-X DVB-S2 Quad Tuner PCIe Card

TBS6909-X is a powerful DVB-S2X/S2 and annex M octa tuner card with PCI Express interface, it is capable of receiving SD/HD digital TV channels from 8 different satellite transponders simultaneously, which is considered as a professional TV tuner for industrial-level users. When you have limited PCIe slots in your server, TBS6909 enables you to receive more channels than the usual dual or quad TV tuner, thus it is highly recommended for IPTV streaming and broadcasting system.



Main Features:

- Support Octa DVB-S/S2/S2X
- Fast scanning functionality for all media
- Support VCM, ACM, CCM, QPSK, 8PSK, 16APSK, 32APSK;
- Support wide band

Applications:

- Data receiving
- IPTV streaming
- Media monitoring
- Digital content distribution



TBS6909-X

Specification:

Model	TBS6909-X	
Connection	PCI-express	
	4x RF in	
DVB-S/S2/S2X		
DVB-S/S2	QPSK	1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10
	8PSK	3/5, 2/3, 3/4, 5/6, 8/9, 9/10
	16APSK	2/3, 3/4, 4/5, 5/6, 8/9, 9/10
	32APSK	3/4, 4/5, 5/6, 8/9, 9/10
DVB-S2X	QPSK	1/4, 1/3, 2/5 (S2-MODCODs)
		1/2, 3/5, 2/3, 3/4, 4/5, 5/6
		8/9, 9/10 (S2-MODCODs)
		11/45, 4/15, 14/45, 7/15, 8/15, 32/45
	8PSK	3/5, 2/3, 3/4, 5/6, 8/9 (S2-MODCODs)
		7/15, 8/15, 26/45, 32/45
	16APSK	2/3, 3/4, 4/5, 5/6, 8/9 (S2-MODCODs)
		7/15, 8/15, 26/45, 3/5, 32/45
	32APSK	2/3, 32/45
	VCM	Yes
ACM	Yes	
Power consumption		
Input/ Power:	12V/7~15W	
temperature	0° ~ 60°	
Other information:		
System Requirements	Windows XP / Vista/ 7/8/10, Linux	
	Available PCI Express x1, x4, x8 or x16 slot	
Dimension:		
TV tuner card size	145*92*1.6mm	
Gift Box Size	200*130*30mm	
Weight	400g	
Package Contents	1* TBS6909-X	
	1* Power cable	